



Distributed by:
Air-Met Scientific Pty Ltd

Air-Met Sales/Service
P: 1800 000 744
F: 1800 000 774
E: sales@airmet.com.au

Air-Met Rental
P: 1300 137 067
E: hire@airmet.com.au
W: www.airmet.com.au

TITAN

The world's first continuous, benzene specific monitor.

Designed to specifically detect benzene in petrochemical environments, providing the ultimate safety monitor for plant & workforce.

The only truly selective wall-mounted benzene monitor

- Fast and accurate detection of benzene down to 0.1 ppm
- Minute by minute sampling providing continuous real-time data
- Robust separation method ensures benzene specific readings
- Internally regulated heating for stable operation at extreme temperatures

Safety

- Clear display & visual alarms for indication of benzene levels
- Two user-definable independent alarm levels including optional real-time STEL calculation
- Two relay outputs provide an immediate warning alarm
- Meets ATEX & IECEx approvals (CSA approval pending)

Ease of use & service

- Modular design for ease of installation and servicing
- Service-free six months operation
- Simple two button interface for menu navigation
- No consumables

Best available photoionisation (PID) detection

- PID independently verified as best performing on the market
- In-built humidity resistance with no need to compensate
- Anti-contamination design for extended field operation



Unrivalled Detection^{ion}.

www.ionscience.com

Following extensive research and development, Ion Science brings to market the world's first fixed, continuous, real-time benzene specific monitor.


Set to change the game in refinery applications, Titan is the first truly selective wall-mounted monitor ranging dynamically from 0.1 ppm to 20 ppm in petrochemical and chemical environments.



Titan receives a sample of gas from the local environment once per minute. Within 60 seconds, the sample is conditioned to enable precise benzene measurement and signal communications.

Titan's continuous, real-time measurement allows trends over time to be monitored and communicated over 4-20 mA or RS485. Data is stored internally for a minimum of two years and can be downloaded remotely to a PC via USB or RS485 for analysis.

Titan provides an immediate warning alarm system with two operator configurable levels, ensuring workers are kept safe and protected to the standards required on site. The instrument incorporates two relay outputs allowing the user to install their own required alarm system.



Titan is designed to be easily installed and serviced. Its modular design allows the Ex d case to be installed well in advance of commissioning. The service module can be removed and replaced as a remotely serviceable plug-and-play cartridge.


Titan incorporates Ion Science's market-leading MiniPID technology with proven resistance to humidity and contamination, ensuring optimal performance whatever the environment.

Applications include

- Oil & gas • Petrochemical • Chemical • Health & safety • Offshore

Accessories

Titan is supplied with an exclusive range of accessories. Visit www.ionscience.com/titan for more info.

TITAN TECHNICAL SPECIFICATION
SENSOR TYPE PID, 10.6 eV lamp coupled with selective filtering
SELECTIVITY Benzene specific within typical petrochemical matrix
RANGE 0 - 20 ppm
MEASURING FREQUENCY One minute
LOWER LIMIT OF DETECTION 0.1 ppm
ACCURACY ± 0.05 ppm or ± 10%, whichever is greater
TEMPERATURE STABILITY Internally heated
SAMPLE FLOW 200 ml/min
DISPLAY Graphical BW LCD 64 x 128 pixels with back light Bright LEDs for normal operation, fault and alarm Two magnetic switches for menu operation
HAZARDOUS AREA SAFETY APPROVALS ATEX/IECEx:  II 2G Ex d II B+H2 T4 Gb (-20 °C to +55 °C)
INGRESS PROTECTION RATING Designed to IP65 (cable gland dependant)
HUMIDITY 0 - 100 % RH
MINIMUM SERVICE PERIOD Selective filter six months PID lamp one year
CABLE ENTRY Two 3/4 NPT gland threads
POWER Vin (nom) 24 V DC @ 3.2 A (recommended) Vin (max) 32 V DC @ 2.4 A Vin (min) 19 V DC @ 4.0 A
COMMUNICATION Isolated 4-20 mA output Isolated RS 485 Modbus (simplex/half duplex or fully duplex) USB when lid removed with PC software
DATA STORAGE On board MMC, minimum of six months
RELAY OUTPUT Two isolated outputs, voltage free, 24 V DC @ 1.25 A max
WEIGHT AND DIMENSIONS 15 kg (33 lbs) 219 x 219 x 172 mm (8.6 x 8.6 x 6.8" approx.)
GAS SAMPLE LINE 10 m max length, PTFE, 6 mm OD, 4 mm ID

Titan V1.0. This publication is not intended to form the basis of a contract and specifications can change without notice.

Distributed by:



Distributed by:
Air-Met Scientific Pty Ltd
Air-Met Sales/Service
P: 1800 000 744
F: 1800 000 774
E: sales@airmet.com.au
Air-Met Rental
P: 1300 137 067
E: hire@airmet.com.au
W: www.airmet.com.au

Manufactured by:
Ion Science Ltd
The Way, Fowlmere,
Cambs, SG8 7UJ, UK
T: +44 (0) 1763 208 503
E: info@ionscience.com
www.ionscience.com

