

Distributed by: Air-Met Scientific Pty Ltd Air-Met Sales/Service P: 1800 000 744 F: 1800 000 774

Air-Met Rental
P: 1300 137 067
E: hire@airmet.com.au
W: www.airmet.com.au



Bladder Pump Controller

Geotech BP Controller 300/500 PSI

The Bladder Pump (BP) Controller (300 or 500 PSI) utilizes advanced electronic logic to control gentle, low-flow sampling. Simple to use, accurate microprocessor controlled FILL/DISCHARGE timers are utilized to recreate expert techniques for low-flow sampling. The BP Controllers are equipped with high-pressure valves and fine resolution regulators that can deliver in remote and deep sampling applications.

BP Controllers connect to any bladder pump system with the use of simple quick-connect adapters.

FEATURES

- · Designed for durable, trouble-free operation
- · High pressure operation for greater depths
- Multiple power input options
- Microprocessor controlled timers for accuracy
- · Internal over-pressure protection
- · Battery over-draw protection
- Water Level Meter compatibility for well draw-down
- · Intuitive user controls and status indicator
- · Accessories cavity for easy portability
- Included: Air-In and Air-Out Hoses, AC Power Supply,
 DC Power Cord and Clip Adapter, Geotech Drawstring Bag



BP Controller 300 PSI with optional draw-down control for low-flow sampling



Geotech BP Controller 500 PSI



Geotech BP Controller 300 PSI

SPECIFICATIONS 300 PSI 500 PSI **Performance Operating Depth** 0-690 feet (210 m) 0 -1000 feet (0-305 m) Input Air Pressure Up to 300 psi (20.5 bar) Up to 500 psi (34 bar) **FILL Timer Range** 5 - 120 seconds 5 - 180 seconds **DISCHARGE Timer Range** 5 - 120 seconds 5 - 180 seconds **Timer Resolution** 2 seconds 2 seconds **Timer Accuracy** ±2 seconds ±3 seconds 12V 8Ah Battery Life 1,300 cycles @ 30 sec. timers 50,000 cycles Internal Battery/Life External only (2x) 9V/30,000 cycles **Environmental Operating Temperature** 32°-158°F (0°-70°C) 32°-158°F (0°-70°C) **Storage Temperature** -40°-185°F (-20°-85°C) -40°-185°F (-20°-85°C) **Physical** Enclosure 7" x 16" x 12" (18 x 41 x 30.5 cm) 7" x 19" x 14" (18 x 48 x 35 cm) Weight 15 lbs. (6.8 kg) 25 lbs. (11.4 kg) **Enclosure Material** Structural resin Structural resin **Input Power External Battery** 10.5-13.8V DC 10.5-26V DC 90-240V AC* 90-240V AC* **Line Frequency** 45-65 Hz 45-65 Hz Maximum Power 15 Watts 15 Watts pulse for 50mS

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.
2650 East 40th Avenue • Denver, Colorado 80205
(303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242
email: sales@geotechenv.com website: www.geotechenv.com

 ϵ

*International AC Power Plug Adapters available (UK, AUS, EURO)