

YSI Pro20

PORTABLE DISSOLVED OXYGEN METER



Dissolved Oxygen and Temperature Meter

The **YSI Pro20** dissolved oxygen (DO) meter is a rugged, user-friendly instrument for dissolved oxygen and temperature measurements. Galvanic and polarographic DO sensors are available for field cables while a self-stirring BOD probe is available for the lab.

In addition to its impact-resistant, waterproof case, the Pro20 has features that make field sampling faster and easier:



User-replaceable cables and sensors



One Touch Cal for DO calibrations within 3 seconds



Quick response times



Distributed by:
Air-Met Scientific Pty Ltd

Air-Met Sales/Service
P: 1800 000 744
F: 1800 000 774
E: sales@airmet.com.au

Air-Met Rental
P: 1300 137 067
E: hire@airmet.com.au
W: www.airmet.com.au



a xylem brand

YSI Pro20 PORTABLE DISSOLVED OXYGEN METER

SPECIFICATIONS W2-03

Pro20 System Specifications (Instrument, Probe, and Cable)	
Temperature	Range -5 to 55°C (0 to 45°C; DO compensation range for mg/L) Resolution 0.1°C Accuracy ±0.3°C
Dissolved Oxygen % Saturation (galvanic or polarographic)	Range 0 to 500% Resolution 0.1% or 1% air saturation (user selectable) Accuracy 0 to 200% air saturation, ±2% of the reading or ±2% air saturation, whichever is greater; 200 to 500% air saturation, ±6% of the reading
Dissolved Oxygen mg/L (galvanic or polarographic)	Range 0 to 50 mg/L Resolution 0.01 or 0.1 mg/L (user selectable) Accuracy 0 to 20 mg/L, ±2% of the reading or ±0.2 mg/L, whichever is greater; 20 to 50 mg/L, ±6% of the reading
Barometer	Range 400 to 999.9 mmHg Resolution 0.1 mmHg Accuracy ±5 mmHg within ±5°C temperature range from calibration point

Pro20 Handheld Specifications	
Size	8.3 cm width x 21.6 cm length x 5.7 cm depth
Weight with Batteries	475 grams
Power	2 alkaline C-cells providing 400 hours of battery life; low battery indicator
Cables	1- 4- 10- 20- 30- and 100-m lengths with military-spec connectors for handheld compatibility (special order up to 100-m)
Warranty	3-year instrument; 2-year cable; 1-year Polarographic sensors; 6-months Galvanic sensors
Salinity Input Range	0-70 ppt; manual (automatically compensates for manual input value)
Data Memory	50 data sets
Languages	English, Spanish, German, French
Certifications	RoHS, CE, WEEE, IP67 waterproof, 1-meter drop test



YSI, a Xylem brand
 1725 Brannum Lane
 Yellow Springs, OH 45387

☎ +1.937.767.7241
 ✉ info@ysi.com
 🌐 YSI.com



YSI.com/Pro20